MULTITASKS


SFM

Stone crusher, forestry tiller and mulcher for PTO tractors with fixed tooth rotor.

The SFM is the answer to a very demanding market and tough applications. This unit combines the functionality and efficiency of a forestry mulcher, forestry tiller and rock crusher. The SFM is equipped with interchangeable bolt-on counter blades, FCP inserts (FAE clade plate) and grill making this machine unique in its category. These options along with FAE's new smoother, more aggressive design differentiate FAE from the rest.

Z style self ranging system of the PTO drive shaft/gearbox

helps keep the correct operating angle between the PTO shaft and the power take-off



Hydraulically controlled rear door adjust final product size while machine is working



Forged and hardened interchangeable counter-blades for longest working life





Adjustable extended 3 point linkage fits perfectly with any kind of tractor

Transmission with side gearbox maximize the power delivered



to the rotor

System protection chains the chains are fixed on plate and these plates screwed to the frame



MAIN OPTIONS



W style self aligning device between PTO drive shaft/gearbox

allows the machine to work at several angles without damaging the PTO



Bolted grid on rear door allows more adjustment of the final material size



Hydraulically adjustable skids allow you to control the rotor depth and prevent material from exiting out the sides



Hydraulic support roller (D. 36 cm - D. 51 cm) helps with compaction and working uneven terrain



160-300 hp




Ø 20 cm max (stones) Ø 35 cm max (trees) Ø 45 cm max (stump)



Depth 30 cm





OPTIONS

Bolted grid on rear hood	Hydraulically adjustable skids	
Bolt-on chain's protection plates	Hydraulic push frame	
High Speed Transmission	Dozing blades	
W style self aligning device between PTO drive shaft/gearbox	Hydraulic support roller	

MODEL	SFM 200	SFM 225	SFM 250
Tractor (hp)	160-300	170-300	180-300
PTO (rpm)	1000	1000	1000
Working width (mm)	2070	2310	2550
Total width (mm)	2390	2630	2870
Weight (kg)	3750	4050	4350
Rotor diameter (mm)	670	670	670
Max shredding diameter stones (mm)	200	200	200
trees (mm)	350	350	350
stump (mm)	450	450	450
Max working depth (mm)	300	300	300
No. teeth type F/3+STC/3/FP	50+6	58+6	62+6

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.







STC/3/FP (side scraper)